

aqua ADIN-20

ADIN-20 PH

- pH meter with proportional regulation • pH range 0÷14
- Microprocessor technology, digital controls and LCD display
- 2 Set-point with independent adjustment with 2 On-Off outputs contact free
- 4÷20 mA output for data recorder or proportional pump • High/low Hysteresis setting
- Programmable Delay • DIN 6 modules housing for panel mounting 106x90x58
- Manual temperature compensation 0-100°C
- pH electrodes not included

ADIN-20 RX

- Redox (ORP) meter with proportional regulation • Redox range 0÷1000 mV
- Microprocessor technology, digital controls and LCD display
- 2 Set-point with independent adjustment with 2 On-Off outputs contact free
- 4÷20 mA output for data recorder or proportional pump • High/low Hysteresis setting
- Programmable Delay • DIN 6 modules housing for panel mounting 106x90x58
- Rx electrodes not included.

ADIN-20 CL

- Free chlorine (residual) meter with proportional regulation • Free Chlorine range: 0 ÷ 10 ppm
- Microprocessor technology, digital controls and LCD display
- 2 Set-point with independent adjustment with 2 On-Off outputs contact free
- 4÷20 mA output for data recorder or proportional pump. High/low Hysteresis setting
- Programmable Delay • DIN 6 modules housing for panel mounting 106x90x58
- Chlorine cells not included
- ADIN-20 CL series has been designed according AQUA chlorine cells A-CG1 and A-CG3

ADIN-20 CD

- Conductivity meter with proportional regulation • Conductivity range: 0 ÷ 10 mS
- Upon request: 0 ÷ 1000µS or 0 ÷ 100µS
- Microprocessor technology, digital controls and LCD display
- 2 Set-point with independent adjustment with 2 On-Off outputs contact free
- 4÷20 mA output for data recorder or proportional pump
- High/low Hysteresis setting • Programmable Delay
- DIN 6 modules housing for panel mounting 106x90x58
- Manual temperature compensation 0-100°C
- CD probes not included

COD	MOD	DIMENSIONS (mm)	PACKING	VOLUME	Kg
		a x b x c			
ADIN20PH	ADIN-20 PH	90x106x58	1	-	0,5
ADIN20RX	ADIN-20 RX	90x106x58	1	-	0,5
ADIN20CL	ADIN-20 CL	90x106x58	1	-	0,5
ADIN20CD	ADIN-20 CD	90x106x58	1	-	0,5
	Upon request IP 65 rated casing available		-	-	-

