

Micro1000 Ratio Turbidimeter

Designed to provide the accuracy demanded in today's laboratory, the **Micro1000** Ratio Turbidimeter is ready to meet the challenge. Features such as the Auto Alert Calibration Prompt and the Quick Connection Lamp Module, allow for simple calibration and low maintenance. A full time ratio (color correction) mode is also featured. With a resolution of 0.0001 NTU at low turbidity readings and an extended range to 10,000 NTU, the **Micro1000** is an ideal and affordable tool for research as well as routine analytical measurements.



Standard Features

- **Extended Auto Ranging Up to 10,000 NTU**
Instrument senses turbidity level of sample and automatically adjusts to the appropriate measurement range.
- **Auto Alert Calibration Prompt**
Automatically prompts the operator to initiate simple menu-driven calibration.
- **Simple Calibration Procedures**
Calibration initiated with the push of a button ensures accurate readings.
- **Ratio (Color Correction)**
Automatic Compensation for background color.
- **RS-232 Output**
Date, time and NTU reading can be captured with a serial printer or data recorder.
- **Reusable ProCal Calibration Standards**
Quick and easy calibration across all ranges without the need to mix Formazin.

Optional Features

- **Pour and Flow Through Assemblies**
Save time by pouring your grab sample through the measurement chamber or pressure feed using the flow through assembly.

Ordering Information

Cat. No.	Description	Approval
20016	Micro1000 IR Ratio Turbidimeter, 100 -240 VAC	ISO7027
20014	Micro1000 WL Ratio Turbidimeter, 100 -240 V Universal Adapter	USEPA

All units include a *ProCal* Calibration Standard set (0.02, 10, 100 and 1,750 NTU), two measuring cuvettes with light shield caps, operator's manual, and plug-in power adapter.

Accessories

39927	<i>ProCal</i> Calibration Set for WL (0.02, 10, 100, 1750 NTU)
39928	<i>ProCal</i> Calibration Set for IR, (0.02, 10, 100, 1750 NTU)
50051	Cuvettes, 28 x 70mm, 3 pack
19975	Pour Through Assembly
19889	Flow Through Assembly
39939	<i>ProCal</i> Calibration Standard, 10,000 NTU (infrared)
39938	<i>ProCal</i> Calibration Standard, 10,000 NTU (White Light)

Specifications

Range:	0 - 10,000 NTU 0 - 2,450 EBC 0 - 10,000 FNU 0 - 10,000 FAU
Principle of Operation:	Nephelometric
Ratio (Color Correction)	Full Time ON or OFF
Accuracy:	± 2% of reading plus 0.01 NTU (0-1,000 NTU) whichever is greater ± 5% of reading (1000 to 4000 NTU) ± 10% of reading (4000 to 10,000 NTU)
Resolution:	0.0001 NTU on Lowest Range
Response Time:	less than 6 seconds
Sample Size:	30 ml
Light Source:	Quick Connect Tungsten Filament or Infrared
Operating Temperature:	32° - 122°F (0° - 50°C)
Air Purge:	Connection for external dry air supply
Outputs:	RS-232 Serial Port
Shipping Dimensions:	14 x 12 x 12 inches (35.5 x 30.4 x 30.5 cm)
Weight:	7.0 lbs. (3.18 kg)
Certification:	UL, CSA, CE, ISO7027

Note: The **Micro1000** meets performance criteria specified by method 180.1 for NTU measurement and ISO7027 (IR version).

Specifications subject to change without notice.



Optional Pour Through Assembly

3170 Metro Parkway
Ft. Myers, FL 33916
Ph: (239) 337-2116
Fax: (239) 332-7643
Toll Free: 888-203-7248
E-mail: hfinfo@watts.com
www.hfscientific.com